

Naturally.



Tap Paste/12-1

# Product Data Sheet

## Binol Tap Paste

**Binol Tap Paste** is environmentally acceptable vegetable oil-based semi fluid grease with high lubricating properties.

The product is recommended for heavy-duty machining at low speed operations, mainly for tapping and drilling.

**Binol Tap Paste** is normally applied with a brush or just by dipping the taps and drills directly in the container.

For a smoother consistency agitation is recommended.

### Physical and Chemical Data (typical)

Analysis	Method	Unit	Results
NLGI			00
Density at 20°C	ISO 3675	kg/m <sup>3</sup>	900
Colour	Optical		yellow
Smell	Nasal		weak
Melting Point	Own	°C	+ 40
Flash Point	SS 150202	°C	330

### Health and Safety Data

Analysis	Method	Unit	Results
Oral toxicity	OECD 401, LD <sub>50</sub>	mg/kg	> 2 000
Aquatic toxicity	OECD 201-203, LC <sub>50</sub>	mg/l	> 100
Biodegradability	OECD 301B	-	readily biodegradable

### Handling

- **Storage** Handling and storage temperatures, approx. +20°C. Storage in closed container, preferably in the original package.
- **Packaging** Plastic container at 15 x 0,5 kg.

A company in the AAK Group

Binol AB  
SE-374 82 KARLSHAMN  
SWEDEN

Phone +46 454 828 00  
Fax +46 454 752070

[binol@aab.com](mailto:binol@aab.com)  
[www.binol.com](http://www.binol.com)

556111-3472  
SE556111347201  
Registered office: Karlshamn

